

Sanders, et al.

January ??, 2002

Quiet Vertical Take Off & Landing (VTOL) Aircraft

Inventors:

Sanders; John K. ^{Jr.} (CM, CA),
 Sanders; J. Kenneth (Hono, HI)

Assignee:

The Idea Creatique (Hono, HI)

Appl. No.:

??????

Filed: Dec.

????

Current U.S. Class:

244/12.1; 244/12.2; 244/12.3; 244/
 23A; 244/23B; 244/45A; 244/91

Intern'l Class:


B64C 029/00-04

Field of Search:

244/12.13, 225, 122, 17.19, 12.2,
 23 C, 12.1, 36, 23 A, 23 R

U.S. Patent Documents

6302230 09/16/2001 Kamen, Dean L., et al.
 6270038 08/07/2001 Cycon; James P., et al.
 62 08/07/2001 Lowe, Charles S., Jr.
 61 01/30/2001 Milde, Jr., Karl F.
 611 09/05/2000 Salinas, Luis A.
 608 07/11/2000 Meek, Stanley R.
 608 07/04/2000 Walter, Wm. C., et al
 607 06/13/2000 Chen, Chung-ching
 606 05/30/2000 Arata, Allen A.
 606 05/23/2000 Day, Terence R.
 606 05/16/2000 Black, Franklin E.
 605 04/25/2000 Yu, Shia-Giow
 605 04/18/2000 Kirla, Stanley J.
 601 01/25/2000 Lowe, Jr., Charles S.
 597 10/26/1999 Libengood, Ronald L.
 589 04/20/1999 Gubin, Daniel
 5890441 04/06/1999 Swinson, Johnny, et al
 5881970 03/16/1999 Whitesides, Carl W.
 5873545 02/23/1999 Kapin, Victor M., et al
 5836543 11/17/1998 Kunkel, Klaus



5836542
 5803199
 5730391
 5730390
 5575438
 5520355
 5503351
 5351911
 5344100
 5318248
 5303879
 5295571
 5213284
 5203521
 5178344
 5170963
 5149012
 5115996
 5102066
 5064143
 5054713
 5046685
 5039031
 4976395
 4955962
 4941628
 4824048
 4804156
 4804155
 4796836
 4795111
 4778128
 4566699
 4461436
 4457476
 4214720
 4196877
 4193568
 4165848
 4117992
 4050652
 4023751
 4014483
 3946970
 3933325
 3871602
 3785592

11/17/1998
 09/08/1998
 03/24/1998
 03/24/1998
 11/19/1996
 05/28/1996
 04/02/1996
 10/04/1994
 09/06/1994
 06/07/1994
 04/19/1994
 11/09/1993
 05/25/1993
 04/20/1993
 01/12/1993
 12/15/1992
 09/22/1992
 05/26/1992
 04/07/1992
 11/12/1991
 10/08/1991
 09/10/1991
 08/13/1991
 12/11/1999
 09/11/1999
 07/19/1990
 04/25/1989
 02/14/1989
 02/14/1989
 01/10/1989
 01/03/1989
 10/18/1988
 01/28/1986
 07/24/1984
 07/03/1984
 07/29/1980
 04/08/1980
 03/18/1980
 08/28/1979
 10/03/1978
 09/27/1977
 05/17/1977
 03/29/1977
 03/30/1976
 01/20/1976
 03/18/1975
 01/15/1974

Burns, David J.
 Walter, Wm. C.
 Miller, Jr., John A., et al
 Plichta, Peter, Buttner, Walter
 McGonigle; Kevin P., et al.
 Jones, Jack M.
 Vass; Gabor I.
 Neumayr, George A.
 Jaikaran, Allan
 Zielonka, Richard H.
 Bucher, Franz
 Blazquez, Jose M. R.
 Webster, Stephen N.
 Day, Terence
 Dlouhy, Vaclav
 Beck, Jr., August H.
 Valverde, Rene L.
 Moller, Paul S.
 Daniel, William H.
 Bucher, Franz
 Langley, Lawrence, et al
 Bose, Phillip R.
 Valverde, Rene L.
 vonKozierowski, Joachim
 Mell, Christian
 Sakamoto, Yujiro, et al
 Kim, Kyusik
 Harmon, Rodney D.
 Moller; Paul S.
 Buchelt, Benno
 Moller, Paul S.
 Wright; Herbert H., et al.
 Cucuzza; Joseph R.
 Messina; Gene
 Andresevit; Frank
 DeSautel, Edwin R.
 Mutrux, Jean L.
 Heuvel, Norman L.
 Bizzarri, Alfredo
 Vrana, Charles K.
 DeToia, Vincent D.
 Richard, Walter A.
 MacNeil, Roderick M.
 Blankenship; Ben F.
 Kaelin, Joseph R.
 Kissinger, Curtis D.
 Kerruish; Kermit D.

Claims

What is claimed is: 1, John Kenneth Sanders, have invented
The ornamental design for

1. A VTOL UFO comprising, as shown and described:

a fuselage having a partial toroidal body having a top, front, rear and bottom ends and a duct, or ducts, extending between the top and bottom surfaces, the fuselage having a longitudinal axis.

a propellerdisk and means, or a series of shrouded impellerdisks and means located in said duct, or ducts, for rotation about its axis, drive means to provide lift for said aircraft. the propellerdisk, or impellerdisks, having a plurality of fixed blades emanating from a central hub to an outer discoidal ring.

a series of three hollowed support struts emanating from an inner wall of the toroidal body for supporting a cone shaped cargo area within the duct and having power and communication cables on embodiments of a single propellerdisk.

a variable system located in line with said duct below said propellerdisk, or impellerdisks, for controlling the direction of the ducted air flow from said bottom openings.

at least a pair of fixed wings attached to said fuselage, at least a portion of the wings being pivotable with respect to the fuselage for flight control.

a landing gear, wheels, pontoons or rails attached to said fuselage.

2. A VTOL UFO of claim 1, comprising: an electric power drive, said drive means comprises: a series of permanent magnets in a bearing system to levitate said propellerdisk, or impellerdisks, at all times and a computer controlled linear induction magnetic bearing located in outer ring of said propellerdisk, or impellerdisks reacting to linear actuators located in said fuselage, used to rotate said propellerdisk, or impellerdisks and provide lift.

3. A VTOL UFO of claim 1 comprising: a vent located at said rear end of embodiments using a single propellerdisk, with means for opening and closing to provide horizontal thrust for use in moving said aircraft in a forward direction.

4. A VTOL UFO according to claim 1 wherein the wings include a fixed portion, and wherein the pivotable portion is a flaperon which is hingedly attached to the aft of the fixed portion and is pivotable with respect to it.

5. A VTOL UFO according to claim 4 further comprising a servo actuator mounted within the fixed portion and engaged with the flaperon for controlling its actuation.

6. A VTOL UFO according to claim 1 further comprising at least one directional vane assembly mounted to and within the shroud downstream from the blades, the directional vane assembly having an outer ring and inner ring bearing being pivotable with respect to the shroud for providing directional control over the flow exiting the duct. At least one adjustable vane with means is connected to the rotatable inner ring for providing additional directional control over the flow exiting the duct.

Technical Field

The present invention relates to manned and unmanned aerial vehicles (UAVs). In particular to a vertical takeoff and landing (VTOL) unusual flying objects (UFOs) having a ducted propellerdisk or series of shrouded impellerdisks for providing zero and low speed horizontal and vertical thrust, and wings with vertical and horizontal stabilizers and air flow vane assembly for providing forward translational lift and thrust in high-speed flight.

Background Of The Invention

There are generally three types of VTOL configurations under current development, a wing type configuration (a fuselage with rotatable wings and engines or fixed wings with vectored thrust engines for vertical and horizontal translational flight), helicopter type configuration (a fuselage with a rotor mounted above which provides lift and thrust) and ducted type configuration (a fuselage with a ducted rotor system which provides translational flight, as well as vertical take-off and landing capabilities).

There is a long list of related inventions, but the most notable pioneers include the Focke-Wulf Fw 61 helicopter in 1936, Piasecki's G-1 tilt rotor in 1951 and Hiller who developed their first flying platform on the basis of a contract awarded in late 1953 by the Office of Naval Research (ONR) for a one-man flying platform. The machine made its first flight in February 1955, and was named the "VZ-1 Pawnee". The

Piasecki Air Jeep, U.S. Pat. No. 2,282,612, developed and flown under the U.S. Army/Navy contracts between 1957 and 1962. In the 1960's Wendell Moore developed the wellknown Rocket Belt which can still be seen at various air shows to this day. The VZ-9-AV Avrocar, U.S. Pat. No. 3,062,482, was funded by both the US Army and US Air Force and was known for it's disk shape which looked very much like a scaled-up modern "Frisbee" toy. Dr. Moller has several designs, his most notable being his M200x, U.S. Pat. No. 3,410,507, for it's flying saucer disk shape and use of multiple engines. Which lead to his series of small ducted fan UAVs, known as Aerobots, U.S. Pat. No. 4,795,111, using a single fan or eight ducted fans, powered by rotary engines. The Airborne Remotely Operated Device (AROD) was a small ducted fan vertical-take-off-and-landing (VTOL) developed by Moller as a subcontractor to Perceptronics, was electrically powered, with power supplied through a tether from the ground station. Which has inspired Helicopter UAV's, the HoverCam can hover over a fixed spatial point and take off and land vertically but have limitations when operated in confined areas due to the exposed rotors rotating above the fuselage. And the Bell/Boeing Eagle Eye Tilt Rotor UAV, a tilted down version and derivative of the Bell/Boeing V-22 Osprey. In 1991 the HOVTOL UAV, U.S. Pat. No. 5,891,111, demonstrates twin high power engines capable of both vertical and horizontal flight using ducted fans primarily for vertical lift. And the Bombardier CL-327 Guardian VTOL UAV, U.S. Pat. No. 5,961,111. It features dual, coaxial, contra-rotating, three bladed rotors. Its design is an evolution of the CL-227 and a follow-on concept, the CL-427 Puma has been proposed. In the late 1980s, Sikorsky Aircraft flew a small nut-shaped UAV named Cypher, U.S. Pat. No. 5,575,438, that was based on coaxial-rotor technology developed by the company in the early 1970s. The Cypher was clearly a flying platform in general concept. The doughnut-shaped shroud not only improved safety in handling the machine, it also helped increase lift. The Cypher II, U.S. Pat. No. 6,270,038, is of similar size to its predecessor, but has a pusher propeller along with its rotor and can be fitted to a configuration with wings for long-range reconnaissance missions.

Other than the electric motor tethered AROD, built by Dr. Moller, all past VTOLs, manned or unmanned, have dealt with loud fuel burning engines as the means of propulsion and the weight issues that go with them. Which separates all others from the current invention which uses new commercially available light weight quiet low voltage linear induction mag-

netic bearings similar to those used for monorails. To hover, the MAGLEV monorails requires less power than its air conditioning equipment. Most new rollercoasters use LIM/LSM: LIM (Linear Induction Motor) and LSM (Linear Synchronous Motor) the two variations of electro-magnetic propulsion. They replace a traditional lift hill and do not contain any moving parts. Typically LIM/LSM systems launch the roller coaster from the station extremely quickly. the fastest at 0-100 in 7 seconds. The high energy density and rugged design of these motors allows their use in demanding installations requiring high duty cycle, high power, rapid acceleration, improved speed and increased performance. Position sensing and control techniques allow for extremely precise control of acceleration and deceleration to permit the safe transport of sensitive or fragile loads. The lack of moving parts and wearing elements (no brushes or sliding contacts) in these motors greatly increases their reliability.

Description

Summary of Invention

The aircraft is made up of 4 primary parts, the top cap of the main body, the propellerdisk (or impellerdisks), the main body (fuselage) and the bottom vane assembly, all built out of a light weight durable composite/plastic. The main cargo area is created by the top cap and the center cone of the main body.

The aircraft uses a magnetic levitation (maglev) bearing system to suspend the propellerdisk (or impellerdisks) between the top cap and the main body at all times. The magnetic bearing system is created by a series of permanent magnet rings, located on the top cap, the propellerdisk (or impellerdisk) and the main body.

A linear induction magnetic power drive is located in the outer edge of the propellerdisk (or impellerdisks), reacting to linear induction actuators located in the main body, which is used to rotate the propellerdisk (or impellerdisks).

Vertical lift in the aircraft is produced by the propellerdisk (or impellerdisks) driving a column of air downwardly, through an annular thrust-flow channel which is formed in the main body of the aircraft.

The annular thrust-flow channel is provided with a flow control vented mechanism at the bottom which is capable of directing the developed air flow in varying orientations be-

tween a substantially vertical (axial) orientation for developing stationary, vertical lift (i.e., hovering) and a vectored (angled) orientation for developing a vertical component for producing lift and a horizontal component for producing forward (or rearward) flight.

The aircraft's main body also has an aerodynamic shape which is capable of developing lift responsive to forward flight using fins and rudders.

The power drive runs on light weight batteries, with a variety of optional rechargers, either by paper thin solar panels on the body of the aircraft or an external battery charger, or by linear generators integrated into the support magnets. The battery industry, which is being driven by the electric transportation and portable consumer electronics industries, is making a substantial investment in battery technology. We will closely monitor the state of the art and will utilize the best available technology when the system design is finalized. Promising technologies include: nickel metal hydride, lithium-ion, and zinc-

Unmanned surveillance aircraft will use a standardized telecommunication system (STS) & standardized robotic system (SR) to control flight & manage audio/video information. Payload consists of the sensor suite, onboard controller, communications, and battery power pack. All communication between the platform and the control station passes through the network payload.

The shape and size of the aircraft is proportional to the size & weight of the maglev power drive which is determined by the cargo (batteries, remote control servos, cpu and cameras).

Advantages of Invention

VTOL UFOs use linear induction magnetic bearings (LIMB) which are ideally suited for propulsion where as they provide superior value compared to other traditional types (ie. gasoline fueled engines and jet turbines). Value is a function of the following:

Lightweight- A LIMB power drive can weigh less than 1/20 of a conventional engine part of which is lost through centrifugal force since most of the power drive is located in the propellerdisk (or impellerdisks).

High Reliability- With magnetic bearings there is no contact between the rotating and stationary parts, meaning there is no wear. These components have design lives far greater than that of conventional bearings and engines. Magnetic bearings are providing high reliability and long service intervals in time critical applications in semiconductor manufacturing, vacuum pumps, and natural gas pipeline compression equipment.

Clean Power- In a magnetic bearing system, polluting exhaust, particle generation due to wear and the need for lubrication are eliminated. There is no gas, oil, grease or solid particles.

High Speed Applications- The fact that a rotor spins in space without contact with the stator means drag on the rotor is minimal. That opens up the opportunity for the bearing to run at exceptionally high speeds, where the only limitation becomes the yield strength of the rotor material. Magnetic bearings have been designed with surface speeds up to 250 m/s or 4.5 million DN, where DN is the diameter of the rotor (mm) times the rotational speed (rpm). In order to achieve one quarter of this kind of speed with conventional bearings, a complex lubrication system is required. No other type of bearing, can match magnetic bearings for shear speed. Magnetic bearings open new possibilities for extreme high-speed applications such as machine tool spindles and turbo compressors.

Position and Vibration Control- Magnetic bearings use advanced control algorithms to influence the motion of the shaft and therefore have the inherent capability to precisely control the position of the shaft within microns and to virtually eliminate vibrations.

Extreme Conditions- The magnetic bearing system, is capable of operating through an extremely wide temperature range. Some have applications as low as -256°C and as high as 220°C, thus allowing operation where traditional bearings will not function. Magnetic bearings can also operate in vacuum where their operation is even more efficient due to lack of windage.

Brief Description of Drawings

FIG. 1A is an exploded cut away perspective view of a single propellerdisk, an embodiment of a VTOL UFO according to the present invention. FIG. 1B is the compiled cut away perspective view of Fig. 1a showing the top of the fuselage (2), the propellerdisk (1), the bottom of the fuselage (3), the vane assembly (4) and how they relate to each other.

FIG. 2A is an exploded cut away perspective view of a single impropellerdisk, an embodiment of a VTOL UFO according to the present invention. FIG. 2B is the compiled cut away perspective view of Fig. 2a showing the top of the fuselage (2), the impropellerdisk (1), the bottom of the fuselage (3), the vane assembly (4) and how they relate to each other.

FIG. 3A is a lower rear perspective view of a single propellerdisk, an embodiment of an unmanned VTOL UFO according to the present invention. FIG. 3B is the top view of Fig. 3a. FIG. 3C is the bottom view of Fig. 3a. FIG. 3D is the side view of Fig. 3a. FIG. 3E is the rear view of Fig. 3a. FIG. 3F is the front view of Fig. 3a. FIG. 3G is an upper front perspective view of Fig. 3a.

FIG. 4A is a side view of a single propellerdisk, an embodiment of a manned VTOL UFO according to the present invention, displaying the cockpit access ladder assembly (13). FIG. 4B is an upper rear perspective view of Fig. 4a. FIG. 4C is an upper front perspective view of Fig. 4a.

FIG. 5A is a lower front perspective view of a pair of joined impropellerdisks, an embodiment of a manned VTOL UFO according to the present invention, displaying a hoverboard configuration with a handlebar flight control assembly (21). FIG. 5B is the top view of Fig. 5a. FIG. 5C is the bottom view of Fig. 5a. FIG. 5D is the side view of Fig. 5a. FIG. 5E is the rear view of Fig. 5a. FIG. 5F is the front view of Fig. 5a. FIG. 5G is an upper rear perspective view of Fig. 5a.

FIG. 6A is a lower front perspective view of a pair of joined impropellerdisks, an embodiment of a manned VTOL UFO according to the present invention, displaying a hoverbike configuration with a handlebar flight control assembly (21). FIG. 6B is the top view of Fig. 6a. FIG. 6C is the bottom view of Fig. 6a. FIG. 6D is the side view of Fig. 6a. FIG. 6E is the rear view of Fig. 6a. FIG. 6F is the front view of Fig. 6a. FIG. 6G is a side perspective view of Fig. 6a.

FIG. 7A is a lower front perspective view of a pair of joined impropellerdisks, an embodiment of a manned VTOL UFO according to the present invention, displaying a hoverpod configuration with a cockpit (14). FIG. 7B is the top view of Fig. 7a. FIG. 7C is the bottom view of Fig. 7a. FIG. 7D is the side view of Fig. 7a. FIG. 7E is the rear view of Fig. 7a. FIG. 7F is the front view of Fig. 7a. FIG. 7G is an upper rear perspective view of Fig. 7a.

FIG. 8A is a lower rear perspective view of three joined impropellerdisks, an embodiment of a manned VTOL UFO according to the present invention, displaying an aircraft configuration with a cockpit (14). FIG. 8B is the top view of Fig. 8a. FIG. 8C is the bottom view of Fig. 8a. FIG. 8D is the side view of Fig. 8a. FIG. 8E is the rear view of Fig. 8a. FIG. 8F is the front view of Fig. 8a. FIG. 8G is an upper front perspective view of Fig. 8a.

FIG. 9A is a lower rear perspective view of four joined impropellerdisks, an embodiment of a manned VTOL UFO according to the present invention, displaying an aircraft configuration with a cockpit (14). FIG. 9B is the top view of Fig. 9a. FIG. 9C is the bottom view of Fig. 9a. FIG. 9D is the side view of Fig. 9a. FIG. 9E is the rear view of Fig. 9a. FIG. 9F is the front view of Fig. 9a. FIG. 9G is an upper front perspective view of Fig. 9a.

FIG. 10A is a lower rear perspective view of five joined impropellerdisk, an embodiment of a manned VTOL UFO according to the present invention, displaying an aircraft configuration with a cockpit (14). FIG. 10B is the top view of Fig. 10a. FIG. 10C is the bottom view of Fig. 10a. FIG. 10D is the side view of Fig. 10a. FIG. 10E is the rear view of Fig. 10a. FIG. 10F is the front view of Fig. 10a. FIG. 10G is an upper front perspective view of Fig. 10a.

FIG. 11A is a lower rear perspective view of six joined impropellerdisk, an embodiment of a manned VTOL UFO according to the present invention, displaying an aircraft configuration with a cockpit (14). FIG. 11B is the top view of Fig. 11a. FIG. 11C is the bottom view of Fig. 11a. FIG. 11D is the side view of Fig. 11a. FIG. 11E is the rear view of Fig. 11a. FIG. 11F is the front view of Fig. 11a. FIG. 11G is an upper front perspective view of Fig. 11a.

Detailed Description Of The Preferred Embodiments

Referring now to the drawings wherein like reference characters identify corresponding or similar elements throughout the several views of the embodiments of the invention. FIG. 1 illustrates cut away perspective views, exploded and compiled, of one embodiment, using a single propellerdisk unmanned VTOL UFO according to the present invention. It includes a single propellerdisk (1), comprising of an outer discoidal ring (1a), a series of propeller blades (1b) attached to the outer ring emanating from an inner hub ring (1c). The outer discoidal ring (1a) houses a permanent magnet ring (15b) used to levitate the propellerdisk a fraction of an inch from a permanent magnet ring (15c) in the fuselage (3). The outer discoidal ring (1a) also houses the linear induction magnetic bearing (16) used to rotate the propellerdisk reacting to the linear induction actuator ring (17) in the fuselage (3). The outer discoidal ring (1a) also houses a ring of batteries or a battery ring (18) to power the linear induction magnetic bearing (16). The inner hub ring (1c) houses three permanent magnet rings (15b) used to levitate the propellerdisk a fraction of an inch from two permanent magnet rings (15a) in the top cap of the fuselage (2) and a permanent magnet ring (15c) in the fuselage (3). These permanent magnet rings (15a-c), which require no power, make the bearing system needed to levitate the propellerdisk at all times including non-operation of the VTOL UFO. The top cap of the fuselage, in this unmanned single propellerdisk embodiment, is made up of a tinted plexiglass dome and a bottom ring that houses the two permanent magnet rings (15a). The top cap (2) attaches to the center cone (3b) of the main body of the fuselage (3) to create the permanent magnet bearing system. The area created within the top cap (2) and the center cone (3b) is the cargo area housing the central processing unit and battery assembly (9) and camera assembly (10). The central processing unit (9) controls all camera and flight control functions via a remote link to the linear induction magnetic bearing (16) and hard wire connections, emanating from the center cone (3b) through the hollowed struts (3a) connected to the inner wall of the outer toroidal fuselage (3), communicating with the linear induction actuator ring (17), the flight control stabilizer fins servos and batteries (6a and 7a), the rear vent servos and batteries (5), the bottom vane assembly servos and batteries (4b and 4e) and additional camera assemblies (11) all located in the toroidal fuselage (3). The bottom vane assembly's outer ring (4d) is attached to the fuselage at the bottom opening of the toroidal duct. A servo (4e) rotates the inner vane ring (4c)

and a second servo (4b) rotates at least one vane (4a, optional three vanes shown in drawings) to redirect the developed air flow in any direction. A rear vent assembly (5) is located at rear of the toroidal fuselage to aid in forward thrust when opened. The VTOL UFO also has at least two attached wings with pivotable portions (6 and 7), used for flight control, which are combined with the landing gear, pontoons or rails (8). An optional telerobotic arm (12) could be attached to the front of the fuselage for special missions.

A ladder assembly (13) is demonstrated in FIG. 4A-C for entering the cockpit (14) of a manned single propellerdisk embodiments of the invention.

Another embodiment of the VTOL UFO demonstrates how multiple propellerdisks can be joined by creating modular shrouded impellerdisks as shown in FIG. 2. The center cone (3b of Fig. 1) is eliminated placing the cargo areas/payloads inbetween the joined impellerdisks (19). Instead of the top cap (2) and bottom fuselage (3) joining in the center hub, they now join around the outside of the impellerdisks (1), which now has a closed hub, creating a toroidal shroud. Optional protective screens (20) can be added to the top and bottom openings of the toroidal duct.

Variations of multiple shrouded impellerdisks are demonstrated in FIG. 5A-G, FIG. 6A-G, FIG. 7A-G, FIG. 8A-G, FIG. 9A-G, FIG. 10A-G, and FIG. 11A-G. Some of which include foldable wing tips with pivotable portions (7) used for added flight control, joystick type flight controls (21), and or cockpits (14).

In addition to the VTOL UFO embodiments described and claimed above, in accordance with alternate embodiments of the invention, scaled up and/or down versions of any of the embodiments heretofore described may be employed for recreational or surveillance purposes, whether or not human subjects are conveyed thereupon or being used as remote controlled UAVs. Such toy versions may be controlled by Standard Radio Controls. The described embodiments of the invention are intended to be merely exemplary and numerous variations and modifications will be apparent to those skilled in the art. All such variations and modifications are intended to be within the scope of the present invention as defined.

CLAIM:
The ornamental design for a VTOL UFO
as shown and described.

John Keith Anderson Jr.